

ZGL060026

Zenith



CHARACTERISTIC / CARATTERISTICHE	
Volt	6V
Capacity / Capacità	20h 12Ah
	5h 10.20Ah
Internal Resistance	Full Charged Battery 25°C ≤10mΩ
Capacity affected by Temperature / Effetti delle temperature sulla capacità	40°C 102%
	25°C 100%
	0°C 85%
	-15° 65%
Self-Discharge 25°C Capacity / Autoscarica a 25°C	after 3 month storage 90%
	after 6 month storage 80%
	after 12 month storage 62%
Charge (Costant Voltage 25°C)	Float Volt 6.8 - 6.9V
	Charge Max. 1.5Amp. 7.2 - 7.5 Volt

CHARACTERISTIC / CARATTERISTICHE			
Battery dimensions / Dimensioni batteria			
L/L	W/P	H/A	Tot - H/A
151	50	93	98
Box Dimensions / Dimensioni scatola			
L/L	W/P	H/A	
-	-	-	
Weight / Peso		1.86Kg	
Terminal / Terminali		F1	
Case / Contenitore		ABS	

Amp. (25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	50.0	34.0	25.0	13.5		7.80		3.31	2.19		1.20	0.64
1.65V	47.4	32.4	23.9	13.0		7.52		3.21	2.14		1.20	0.64
1.70V	44.7	30.7	22.8	12.4		7.22		3.10	2.08		1.18	0.62
1.75V	41.9	29.0	21.6	11.8		6.90		2.98	2.02		1.15	0.60
1.80V	39.1	27.2	20.4	11.2		6.57		2.85	1.95		1.12	0.58


Watts (25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	88.0	59.2	47.7	26.8	21	15.6	9.78	6.60	4.37			
1.65V	82.5	55.7	45.1	25.9	20	15.1	9.49	6.42	4.26			
1.70V	77.1	52.3	42.5	24.5	19	14.4	9.17	6.22	4.10			
1.75V	71.7	48.8	39.8	23.1	18	13.8	8.81	6.00	3.96			
1.80V	66.4	45.4	37.2	21.9	17	13.4	8.43	5.76	3.82			


This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact U.B.S. UNION BATTERY SERVICE for the latest information.

Le informazioni contenute in questa scheda tecnica sono solo descrittive e indicative, non sono una garanzia. U.B.S. UNION BATTERY SERVICE si riserva il diritto di aggiornarle/modificarle senza preavviso.







Charging characteristics



Temperature effect on battery self-discharge



Discharge characteristics (25°C)



Temperature effect on capacity

